

Australis 26™ Scanning Receiver

The Australis 26k Scanning Receiver is the preferred choice worldwide for those people who need to find a VHF transmitter under all conditions. It's superior signal receiving abilities are combined with durability in a lightweight housing with LCD display.

The receiver comes with a heavy duty leather case that can be carried around the neck or from a belt. The battery pack consists of rechargeable NiCad batteries with an operating life of around 14 hours before requiring a recharge of four hours at fast charge rate. Spare rechargeable battery packs are available and a battery holder to use with dry cells as required.

The Australis 26k is capable of detecting signals over four adjacent frequency bands and has the ability to automatically scan through up to 100 transmitter frequencies. This is an invaluable feature when tracking animals. The Australis 26k can also be used in the normal manual mode, if preferred, searching for one transmitter at a time.

FEATURES

- ▶ Headset – two 3.5mm phone jacks, one disables the audio outputs loud speaker
- ▶ Memory – retention memory is retained while receiver is switched off and while battery packs are changed
- ▶ Low battery indicator (beep notification)
- ▶ External socket – data logging and remote control
- ▶ Display – a graphic type liquid crystal display approximately 18mm x 16mm; displays all frequency, signal strength and mode data; LED back lighting which can be switched on for night viewing
- ▶ Volume control – conventional knob operated potentiometre with on/off switch
- ▶ Gain control – knob operated potentiometre (gain reduction: 50dB)
- ▶ Leather case



SPECIFICATIONS

Frequency Ranges:	148.000 - 151.999MHz 149.000 - 152.999MHz 160.000 - 163.999MHz 170.000 - 173.999MHz
Frequency Selection	1kHz steps with fine tuning in 100Hz
Frequency Memories	10 banks of 10 memories with fine tune offset stored for each frequency
Memory Scanning Rate:	Can be set to 1.25; 2.5; 5 or 10 seconds (default 1.25 sec/chn)
Audio Output :	250mW into internal loudspeaker or external load
Size	50mm (H) x 145mm (W) x 170mm (D)
Weight	<1kg

Titley Scientific Australia

PO Box 133
Lawnton QLD 4501
+61 07 3881 5577
info@titley-scientific.com

Titley Scientific USA

601 Business Loop 70, Suite 110
Columbia, Missouri, 65203-2546
+1573 442 8745
usa@titley-scientific.com

Titley Scientific UK

Llanmaes Estate Office
St Fagans, Cardiff, CF5 6DU
+44 2920 022 099
uk@titley-scientific.com